

## Communications & Power Industries - Microwave Power Module

The PTXM9754 is an ultra compact modular **Microwave Power Module** with an integrated “Super Mini” Travelling Wave Tube (TWT), a solid state preamplifier and an optimised high density switch mode power supply to produce a single “drop-in” microwave amplifier block.

Integration of TWT and Power supply simplifies the system designer’s task by eliminating TWT interconnections (and their associated safety and reliability hazards). Integration further reduces the overall system size, simplifying the installation task.

The MPM is factory adjusted to optimise TWT performance. No user adjustments are required, simplifying replacement and reducing replacement times in the field.

The MPM can be configured to incorporate a variety of TWT models, allowing the user to specify frequency and peak power parameters.

The PTXM9754 features a broad band (6.0 to 18 GHz) TWT capable of providing 100 W CW across the band. A low gain TWT is specified together with a low noise Solid State Preamplifier to provide optimum noise performance.

The MPM includes a high speed focus electrode modulator to permit operation at high PRFs. This makes the MPM ideal for pulsed applications such as ECM and Radars.

A control interface is incorporated which allows remote operation and status monitoring, providing diagnostic outputs for BIT purposes.



The PTXM9754 is an ultra compact modular Microwave Power Module with an integrated “Super Mini” Travelling Wave Tube (TWT)

### FEATURES:

- In addition to a very small size and light weight, the unit features excellent thermal management. High electrical efficiency requires minimum cooling and provides high reliability service over a wide temperature range.

### BENEFITS:

- By virtue of the fully encapsulated high voltage section, the unit can operate at high altitudes and high humidity.

### APPLICATIONS:

- These Microwave Power Modules are fully tested to agreed acceptance test procedures before shipment, meeting the demands of high performance Radar and ECM systems.

## RF Characteristics

Typical Operating Characteristics for the MPM incorporating a 100W 6.0 to 18 GHz TWT <sup>Note 1.</sup>

Frequency Range	6.0 to 18.0 GHz
RF Output Power (Saturated)	100W minimum (+50.0 dBm) (6.0 to 18.0 GHz)
Duty Cycle	100% max
Small Signal Gain	63 dB nom, 58dB min, 70dB max
RF Input Power (for saturation)	0 ± 1 dBm
Second Harmonic at saturation	
	-3 dBc max (from 6.0 GHz)
	-6 dBc max (from 7.5 to 10.0 GHz)
	-10 dBc max (from 10.0 to 18.0 GHz)
Noise Power Density (Beam On)	-32 dBm/MHz max
Noise Power Density (Beam Off)	-110 dBm/MHz max
Maximum spurious PM measured in a 100 Hz bandwidth	-45 dBc
Phase Noise Power Density	
	-100 dBc/Hz max at 1 kHz from carrier
	-110 dBc/Hz max at 10 kHz from carrier
	-120 dBc/Hz max at >100 kHz from carrier
Noise Figure	15dB (typical)
Input VSWR	2.0:1 max
Output VSWR	2.5:1 max

Load VSWR	2.0:1 max (No damage)
Pulse Width	0.1 to ∞µs (CW Operation)
Pulse Delay (ON command to RF Out)	150 ns max
Pulse Repetition Frequency (PRF)	30 kHz max

## Prime Power Requirements

Prime Power	28 V DC Per MIL-STD-704E
Power Consumption	540 W maximum

## Connectors

Primary Power Input Connector	D-sub, male, 15-way
Control and Monitoring Connector	D-sub, female, 15-way
RF Input Connector	SMA Female
RF Output Connector	TNC Female

## Control and Monitoring

Control Inputs	HV ON RF ON BATTLE OVERRIDE
Status Outputs	HV OK FAULT WARMED UP

Notes:

1 Other Characteristics are available to special

## Fault Protection

Internal Built-in Test incorporated to monitor most TWT parameters and trip at collector overtemperature. MPM shuts down under fault conditions. Helix current can be monitored by the end user to aid TWT troubleshooting.

TWT Monitor Outputs	Helix Current
Heater Warmup	180 Seconds from power up
Automatic Restart	Auto-reset after fault is included (3 restarts).

## Mechanical

Mechanical Outline	203.2 x 196.85 x 35.6mm excluding fixings and connectors -45 dBc
Weight	2.6 kg max
Orientation	Any
Finish	Nickel plated
Markings/Labels	Type Number Model Number Serial Number Connector Ident. Hazard Warning
Cooling	Conduction, via base-plate; +85°C maximum collector temperature

## Options (available on request)

Alternative prime power: 270V DC, 115V AC 60Hz  
 Alternative monitor outputs: TWT Overtemp, Cathode voltage, Standby indicator  
 Additional control inputs: PSU sync signal

## Environmental

Ambient Temperature (operating)	-25 to +85°C
Ambient Temperature (Non-operating)	-40 to +100°C
Baseplate Temperature (MPM) (operating)	85°C maximum
Altitude (Operating)	0 - 10,000 ft
Vibration (Operating - 3 axes)	0.04 g <sup>2</sup> /Hz 40 to 2000 Hz -6dB/octave 1000 to 2000 Hz
Shock (3 axes)	20 g, 11 ms half sine
Humidity	90%, non-condensing
EMC Performance	MIL-STD-461E- Requires external EMC filter



**TMD Technologies Division**  
 Unit 3 Swallowfield Way  
 Hayes, Middlesex  
 United Kingdom  
 UB3 1DQ

tel: +44 (0)20 8573 5555  
 email: [wecare@tmd.co.uk](mailto:wecare@tmd.co.uk)  
 web: [www.cpii.com/tmd](http://www.cpii.com/tmd)

For more detailed information, please refer to the corresponding TMD technical description if one has been published, or contact TMD. Specifications may change without notice as a result of additional data or product refinement. Please contact TMD before using this information for system design.